

## Hesse ANTISLIP CLEANER PR 93

### >Product description

High-yield cleaning and care concentrate based on pH-neutral and biologically degradable surfactants. This product retains the surface's existing anti-slip properties.

### >Areas of application

For parquet and wooden floors, as well as laminates, PVC, tiles and plastic surfaces.

### >Surface Preparation

Surface preparation	Remove adhering particles from the surface to be cleaned with a cloth or a soft brush. For basic cleaning of water-soluble soiling, add Hesse INTENSIVE-CLEANER PR 91 or Hesse REMOVER OS 5600 to the cleaning water and use this to clean the floor.
---------------------	---

### >Finishing

#### >Times

conditions of transport	frost-free - up to a maximum of 35 °C
Accessible after	1 h / 20 °C

### >Application

Application
other treatment
other treatment

### >Processing instructions

Add cleaning water for regular cleaning and use this solution for moist but not wet wiping. The surface must be cleaned and protected in one operation. Maintenance or regular cleaning and care: dilute the cleaner in water at a ratio of 1 : 100 (100 ml to 10 l of water) for lesser soiling. Intensive cleaning: mix up to at most 1 : 10 (100 ml to 1 l of water) for heavy soiling or for more intensive care. Stain removal: dilute PR 93 in some water for coffee, tea, milk, fruit juice, urine and blood.

### >Technical data

Flow time (+/- 15 %)	21 no information
Appearance	not relevant
Density series kg/l	1.001
Form of delivery	fluid
Non-volatile content series %	2.6
VOC EU %	0 %
VOC FR	C
Storage temperature	10 - 40 °C
Shelf life in weeks	52
conditions of transport	frost-free - up to a maximum of 35 °C
Working temperature	20 °C

### >Ordering information

Order number	Gloss level 60° (Gloss)	Container Size
PR 93	-	1 l, 25 l

### >Particular instructions


Keep locked away and out of the reach of children! Containers should only be put out for recycling when they have been completely emptied.

## Hesse ANTISLIP CLEANER PR 93

### >General information

Cleaning and care instructions: please observe the care instructions as per DIN 18356. Wipe parquet using a slightly damp but not wet cloth. Please use only neutral, silicone-free, ammonia-free and non-abrasive cleaners. Regular care and cleaning with Hesse ANTISLIP-CLEANER PR 93 increases the life of the sealant and retains the surface's anti-slip properties. Surfaces tested to anti-slip class R10: PURA-NATURA HDE 52-0 (+ 10 % HZ 75), HYDRO-PUR PRIMO HDE 54004 (+ 10 % HZ 75), HYDRO TOP-SEAL HE 65094 (+ 10 % HZ 75), FLOORCARE-OIL OE 52062, NATURAL-OIL OE 52832, SPEEDCARE-OIL OE 52872. Please refer to the test certificates for the precise information.

### >Particular properties and/or testing standards

Test standard / basis	Testing laboratory	Mark	Report	No.
Non-slip class R11 per DIN 51130	SFV		Test certificate number	82611802.001 / -04.001 / -06.001 / -08.001 / -10.001 / -12.001

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at [www.hesse-lignal.de](http://www.hesse-lignal.de) or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.