

Sepa[®] basic / Sepa[®] basic edition

Watertight, non-breathable underlays



Sepa[®] basic and Sepa[®] basic edition are 2-layer, non-breathable roofing underlays suitable for unboarded cold pitched roofs. They stand out for low-cost price maintaining the well-known Klöber product quality.

Product features & benefits

- Watertightness, already in the low-end segment
- Coating against wood preservatives
- Anti-condensation with back-fleece
- High UV-resistance
- Reduced flapping noises compared to competitors
- Best in class regarding product appearance

Area of application

Suitable for unboarded cold pitched roofs.

Material

2-layer, PP membranes

Roll size

50m x 1.50m (75m²)

Packaging

42 rolls/pallet

Product codes

KU 0810

KU 0815

Certification

- CE certified

TECHNICAL DATA



	Sepa [®] basic		Sepa [®] basic edition	
Weight	100g/m ²		90g/m ²	
Water vapour transmission EN 12572 (s _d value)	> 15m		> 15m	
Reaction to fire EN 13501-1, EN 11925-2	E		E	
Water column, EN 20811	1800mm		1800mm	
Resistance to water penetration EN 1928	W1		W1	
Tensile strength longitudinal / transverse EN 12311-1	200N/50mm	170N/50mm	185N/50mm	155N/50mm
Elongation longitudinal / transverse EN 12311-1	60%	60%	60%	60%
Resistance to tearing (nail shank) longitudinal / transverse EN 12310-1	125N	125N	110N	110N
Resistance to temperature	-40°C to +80°C		-40°C to +80°C	
UV-resistance ¹⁾	4 months		4 months	

¹⁾ Natural weathering Central Europe.

TS-09#38-EN-1112. Für Druckfehler wird keine Haftung übernommen. *Eingetragenes Warenzeichen der Klöber GmbH.